
Prometheus a c o u s t i c s



Prometheus bring fire to your music



Bring fire to the music

Prometheus audio system reveals more of true music beauty inside of your listening space, whenever you create, mix or listen to it.

Its advanced acoustics breaks through the physical limitations of conventional speakers in pursuit of ultimate sound quality in every listening conditions.



Innovation

Ingenious acoustical arrangement of Prometheus reduces negative impact of the listening room and improves the subjective perception of music.

Four strategically placed mid-woofers literally redirect mid- and low-frequency sound energy toward the listener, rather than sending it around, towards nearby surfaces that reflect sound in an uncontrolled way. You can place them wherever you want, even right next to the wall.

Prometheus is not only about loudspeakers.

It is a complete, active, stereo audio system. Just plug it into mains and provide the audio signal from your favourite source to enjoy your music. Like never before.





Design

Be mesmerized with these finely-crafted, ageless style cabinets.

One of a kind anatomic shapes form elusive form-factor and perfect acoustical properties of Prometheus speakers.

Prometheus audio system is housed in just two sleek bodies with $20\,\mathrm{x}\,30\,\mathrm{cm}$ footprint, that carry sound potential of big floor-standing speakers.

Speaker - rebuilt

Acoustics - reinvented

Sound – rediscovered

Integrity

Here it is, perfectly integrated audio stereo system.

It encloses audiophile grade ADC / DAC with ultra-low noise and jitter. Packs 3 channels of high-end amplification with up to 600 W of average output power per box. Boasts 10 high-performance speaker driver units in your stereo system.

In effect, provides effortless dynamics of big floorstanding columns with 10-inch woofers. Innovative acoustics is included as a bonus.







Class-D amplifiers with 600 Watts per box

Unlimited power at audiophile quality.

High power density, green technology without sonic qualities degradation.

Four high-performance, long-excursion woofers

All woofers in the box contribute to bass output.

Clean reproduction of live performance volume, large dynamics headroom.

Advanced 3D-image waveguide

Linearizes dispersion of high frequencies up to ultrasonic range. Silky smooth high tones with large spatial coverage.

Vertical MTM layout

Narrows down vertical dispersion of midrange frequencies. Improves in-room sound intelligibility, widens musical soundstage.

Rounded box edges

Prevents diffraction normally occurring at the speaker box edges.

Allows the speakers to disappear inside of the holographic soundstage.

No speaker drivers on the rear panel

Enables positioning in close proximity to the wall.



Dual side-firing woofers

The symmetrical, back-to-back coupled woofers cancel the reaction forces generated by the vibrating cones and completely prevent cabinet vibration. The box does not contribute to the sound of the loudspeaker drivers.

Bass & midrange controlled directivity

Cuts unwanted acoustical emission at extreme angles.

Prevents harmful reflections from mixing with direct sound at the listening spot.

Bass & midrange controlled power response

Makes the spectrum of diffuse sound similar to direct sound.

Immunizes the speaker's sound signature against harsh acoustic environment.

Two-plane symmetrical driver array

Forms point-like apparent sound source.
Achieves spatial and time coherence of the sound source.

Non-resonant speaker compartment

Prevents any standing waves occuring inside due to its unique geometry. Devoid of sound coloration due to internal speaker cabinet resonances.

Technical specification

Speakers

tweeter: 1" waveguided aluminium dome front woofers: 2x5.25" aluminium cone

side woofers: 2x6.5" high-excursion aluminium cone

Enclosure

sealed, DSP-controlled bass-midrange cardioid construction: structure-hardened HDF, CNC machined available finish: matte black / matte white lacquered dimensions: (H x W x D) $450 \times 200 \times 300$ mm

weight: 16 kg/pc

Amplifier

3-channels, class-D Hypex NCore with SMPS front woofers: 250 Wrms / 4 Ohm @ 0,1% THD side woofers: 250 Wrms / 4 Ohm @ 0,1% THD tweeter: 100 Wrms / 4 Ohm @ 0,1% THD

Power supply

operating mains voltage: 100-120, 200-240 VAC / 47-63 Hz power consumption (maximum, per speaker): 650 W standby power consumption: 0,5 W

Connectivity

supported sample rate up to 192 kHz / 24 bit

1 x S/PDIF (RCA)

1 x S/PDIF (Toslink)

1 x AES3 (XLR)

1 x analog (RCA + XLR)

1 x S/PDIF (RCA) / AES3 (XLR) output for stereo sync micro USB type-B for EQ / tuning upload

Analog audio

XLR max input level: 6,15 Vrms RCA max input level: 2,18 Vrms


Digital audio

digital input latency: 1,8 ms

IR remote control

ON / OFF volume control source select 3 tuning presets mute







From now on, you can only look for music.

